Dart Aerospace Ltd. Monday, 6/5/2006 7:26:57 AM Kim Johnston **Process Sheet** Customer : CU-DAR001 Dart Helicopters Services **Drawing Name** : ASPIRATOR Job Number : 27331 **Estimate Number** : 12424 : NIA : D2000109 P.O. Number **Part Number** : D2000-109 REV A1 S.O. No. : N/A : 6/5/2006 This Issue **Drawing Number** Prsht Rev. Project Number : N/A : NIA : PURCHASED PARTS First Issue **Drawing Revision** : NIA **Previous Run** Material : 7/29/2006 **Due Date** Written By Checked & Approved By Comment : Est Rev:A **Additional Product** Job Number: Description: Seq. #: Machine Or Operation: 1.0 PG **PURCHASING** Comment: PURCHASING Issue P/O: 1406 For D2000-109 Spin as per Dwg D2000-109 C206/05/06 Possible Supplier: SIEG Material release note is required 2.0 D2000109S Aspirator- Outer Flange Comment: Qtv.: 1.0000 Each(s)/Unit Total: 1.0000 Each(s) PACKAGING 1 PACKAGING RESOURCE #1 3.0 Comment: PACKAGING RESOURCE #1 Receive & Inspect For Transit Damage CJ06/14/06 Ensure material certification is attached 4.0

QC6

DIMENSIONAL CHECK

Comment: DIMENSIONAL CHECK

5.0 SMALL FAB SMALL & MEDIUM FAB RESOURCE 1

Comment: SMALL & MEDIUM FAB RESOURCE 1

Drill as per Dwg D2000

Deburr

SAN

Each

Dart Aerospace Ltd

W/O:		WORK ORDER CHANGES								
DATE STEP		PROCEDURE CHANGE	Ву	Date	Qty	Approval Mfg / Design Mgr	Approval QC Inspector			
				<u> </u>	<u> </u>					

NCR:		WORK ORDER NON-CONFORMANCE (NCR)									
		Description of NC	Corrective Action Section B			Verification	Approval Design Mgr	Approval QC Inspector			
DATE	STEP	-' Section A Initial Action Description Sign		Sign & Date	Section C						
				,							
				•							

Part No:	PAR #:	Fault Category: NCR:	Yes No DQA:	Date: <u>06/06/39</u>
NOTE: Date & initial all entries		•	QA: N/C Closed:	Date:
				بسنرني


Date Monday, 6/5/2006 7:26:57 AM Uşer: Kim Johnston **Process Sheet** Drawing Name: ASPIRATOR Customer: CU-DAR001 Dart Helicopters Services Job Number: 27331 Part Number: D2000109 Job Number: Seq. #: **Machine Or Operation:** Description: INSPECT WORK TO CURRENT STEP 6.0 QC5 6006.221 Comment: INSPECT WORK TO CURRENT STEP PACKAGING RESOURCE #1 7.0 PACKAGING 1 Comment: PACKAGING RESOURCE #1 Identify and Stock Location:_ 8.0 DC DOCUMENT CONTROL Doctours 128 Comment: DOCUMENT CONTROL Inspection Level 21 Job Completion

Dart Aerospace Ltd

W/O:		WORK ORDER CHANGES							
DATE	STEP	PROCEDURE CHANGE	Ву	Date	Qty	Approval Mfg / Design Mgr	Approval QC Inspector		
		·							
<u></u>									
		•							

NCR:		WORK ORDER NON-CONFORMANCE (NCR)								
		STEP Description of NC		Corrective Action Section B	Verification		Ammerical			
DATE	STEP	Section A	Initial Design Mgr	Action Description Design Mgr		Section C	Approval Design Mgr	Approval QC Inspector		

Part No:	PAR #:	Fault Category:	 NCR:	Yes	No	DQA:	 Date: _	
NOTE: Date & initial all entries				QA: I	V/C C	losed:	 Date: _	
							*	



11

COPIED Copyright @ 2000 by DART AEROSPACE LTD IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD. DOCUMENT THIS

FORM: 1005 WORK ORDER: UY2370

COPPER AND BRASS SALES MATERIAL TYPE ALUMINUM ALLOYS WITH LOW BERYLLIUM

PRODUCT DESIGNATION
2014 2024 2224 2324 7050 7075 7150 7175 7475
ALUMEC 89 ALUMEC 99 QC-7

"WARNING"

SMALL CHIPS, FINE TURNINGS AND DUST MAY IGNITE READILY. EXPLOSION POTENTIAL MAY BE PRESENT WHEN: DUST OR FINES ARE DISPERSED IN THE AIR; FINE, DUST OR MOLTEN ALUMINUM ARE IN CONTACT WITH CERTAIN METAL OXIDES; OR, CHIPS, FINES, DUST OR MOLTEN ALUMINUM ARE IN CONTACT WITH WATER OR MOISTURE. KEEP AWAY FROM IGNITION SOURCE. USE EXPLOSION-PROOF VENTILATION. KEEP MATERIAL DRY.

THIS PRODUCT CONTAINS BERYLLIUM AND COPPER. INHALING BERYLLIUM DUST OR FUMES MAY CAUSE CHRONIC BERYLLIUM DISEASE (CBD), A SERIOUS CHRONIC LUNG DISEASE IN SOME INDIVIDUALS. BURYLLIUM IS A CANCER HAZARD; OVER TIME CBD AND CANCER CAN BE FATAL, TARGET ORGAN IS PRIMARILY THE LUNG. INHALING LARGE AMOUNTS OF COPPER, MAGNESIUM OXIDE, MANGANESE OXIDE, AND ZINC OXIDE FUMES OR DUST MAY CAUSE METAL FUME FEVER WITH FLU-LIKE SYMPTOMS. CHRONIC OVEREXPOUSURE TO COPPER MAY CAUSE THICKENING OF THE SKIN; AND SKIN, TEETH, AND HAIR DISCOLORATION. CHRONIC OVEREXPOUSURE TO MANGANESE DUST CAN CAUSE CENTRAL NERVOUS SYSTEM DAMAGE, SCARRING OF THE LUNGS AND REPRODUCTIVE HARM IN MALES. TARGET ORGAN IS PRIMARILY THE LUNG, BUT REPEATED HIGH EXPOSURE CAN ALSO AFFECT THE LIVER. CHRONIC OVEREXPOSURE TO IRON OXIDE DUST/FUME MAY CAUSE LUNG SIDEROSIS. CHRONIC OVEREXPOSURE TO SILICON DUST CAN CAUSE CHRONIC BRONCHITIS. OVEREXPOSURE TO AMORPHOUS SILICA CAN CAUSE DRYING OF THE MUCOUS MEMBRANES OF THE EYES, NOSE, AND THROAT.

THIS PRODUCT ALSO CONTAINS NICKEL AND CHROMIUM COMPOUNDS. INHALATION OF NICKEL DUST OR FUME MAY RESULT IN INFLAMMATION OF THE RESPIRATORY TRACT AND CAUSE NASAL AND/OR LUNG CANCER. NICKEL HAS BEEN IDENTIFIED AS A POTENTIAL HUMAN CARCINOGEN. EXPOSURE TO CHROMIUM DUST OR FUME MAY CAUSE METAL FUME FEVER WITH FLU-LIKE SYMPTOMS AND KIDNEY AND LIVER DAMAGE. UNDER HIGH TEMPERATURES, HEXAVALENT CHROMIUM MAY BE PRODUCED, IF IN THE INSOLUBLE FORM, IT IS A CONFIRMED HUMAN CARCINOGEN. (CALIFORNIA PROPOSITION 65).

IF COATED WITH OIL, MAY CAUSE SKIN IRRITATION/DERMATITIS BY CONTACT. WELDING FUME IS LISTED AS A POSSIBLE CARCINOGENIC TO HUMANS.

READ THE ALUMINUM/ALUMINUM ALLOYS MATERIAL SAFETY DATA SHEET(MSDS) ON FILE WITH YOUR EMPLOYER BEFORE WORKING WITH THIS MATERIAL

- * If processing or recycling produces particulate, use exhaust ventilation or other controls designed to prevent exposure to workers. Examples of such activities include melting, welding, grinding, abrasive sawing, sanding and polishing. Any activity which abrades the surface of this material can generate airborne particulate. Use respiratory protection (P100, quantitative fit testing required) if exposures exceed the permissible limits.
- * The Occupational Safety and Health Administration (OSHA) have set mandatory limits on occupational exposures.
- * Aluminum, in solid form and as contained in finished products presents no special health risk.
- Sold for manufacturing purposes only. This product can be recycled; contact your sales representative.

The Occupational Safety and Health Administration require employers to provide training in the proper use of this product.

For additional information, call or write to Copper and Brass Sales, 22355 West Eleven Mile Road, Southfield, MI 48034, telephone 248-233-5600, or visit our web site @ www.copperandbrass.com.

1100 Aluminum Coll and Sheet

1100 Aluminum Coll and Sheet

Alloy Attributes

- Commercially pure aluminum
- Low strength, but excellent corrosion resistance
- Unmatched in workability
- Good welding, brazing, and soldering

Tempers

- 0 Annealed
- H14 Strain hardened and stabilized to a 1/2 hard temper

Shapes / Forms

· Coil and Sheet

Sizes/ Tolerances

Coil Thickness:

0: .016, .020, .032, .040, .050, .063, .080, .090, .125, .190 H14: .016, .020, .025, .032, .040, .050, .063, .125, .190

Sheet Thickness:

0: .020, .025, .032, .040, .050, .063, .080, .090, .125, .190 H14: .016, .020, .025, .032, .040, .050, .063, .090, .125, .190, .249

Sheet Width and Length: various sheet sizes; 36" and 48" wide coil

Folerances: (Please note - all domestic mills produce as half-commercial tolerance on the minus side). Example- Alcoa .063 (48" wide) is +.000-.0035

Malassia) []
Material Thickness	36" Wide	498145
.016		48" Wide
020/00-	+001	+0015
020/.025	+ 0015	
.032		+002
.040	+002	+0025
.040	+0025	
.050, .063		+0035
.071	+003	+0035
	+0035	4 004
.080, .090		+004
.100, .125	+0035	+0045
. 100, 125	+0045	
		+006

Arm Arman man man (601) 230 - quan

- Mexinox
- Thyssen-Krupp Nirosta
- Allegheny-Ludium

Mechanical Properties

Tensile (ultimate) strength, yield strength, elongation

Minimum Tensile

Minimum Yield

25,000 PSI

% Elongation Rockwell Hardness

40%

B95 Max

Physical Properties

70,000 PSI

- Coefficient of Thermal Expansion: 9.4
- Electrical Conductivity: 74%
- Coefficient of Thermal Expansion: 10.3
- Weldability: Very good
- Formability: Good

Nominal Chemical Composition

- 0.03% maximum C
- 2% max Mn
- .75 % max Si
- 16-18% Cr
- 10-10.5% Ni
- 2-2.5% Mo
- Balance Fe

.160, .190 +-.007 +-.008 .249 +-.012 +-.014

Product Surface Finishes

Mill Finish

Dedicated Suppliers

- Alcos
- Commonwealth Aluminum
- Offshore suppliers (various)

Mechanical Properties

- Tensite (ultimate) strength, yield strength, elongation
- 0 Temper

Tensile	Modulus of Elasticity	Yield	Shear Strength	% Elongation	Brinell Hardness
13,000 KSI	10	5,000 KSI	9,000 PSI	35%	23
• H14					
Tensile	Modulus of Elasticity	Yield	Shear Strength	% Elongation	Brinell Hardness
18,000 KSI	10	17,000 KSI	11,000 PSI	9%	32

Physical Properties

- Coefficient of Thermal Expansion: 13.1 x 10-6 in/in/°F
- Thermal Conductivity: 1540 BTU/Ft/Hr/Ft2/°F
- Nominal Density: .098 lb./in3
- Electrical Conductivity: 59% IACS

Nominal Composition

- .10% Cu
- 99.0% minimum aluminum